



Scotch-Weld™

Spray 75 Repositionable Adhesive



Product Data Sheet

Updated : August 1995

Supersedes November 1993

Product Description

Spray 75 Adhesive is a pressure sensitive aerosol adhesive suitable for temporary holding or positioning of lightweight materials for display, or prior to final assembly.

The product, when sprayed on one surface has a bonding range from 5 seconds to several hours, and its low peel strength allows for even lightweight materials or tissues to be lifted and repeatedly repositioned.

Spray 75 Adhesive is a clear adhesive which will not bleed through, stain or wrinkle materials. This adhesive does not embrittle with age.

Physical Properties

Not for specification purposes

Solvent	Petroleum Distillates	
Flash Point	-46°C	
Propellant	Hydrocarbon	
Contents	325g (500ml)	
Solids Content	Typically 10%	
Spray Pattern	Particle	
Colour	Clear	
Shelf Life	12 months from date of receipt by customer when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

Performance Characteristics

Not for specification purposes

Water Resistance	Good	
Weathering Resistance	Good	
Fuel and Oil Resistance	Poor	
UV Light Resistance	Good	

Additional Product Information

Does not contribute to ozone depletion.

Storage Conditions

Cool dry place. Storage temperature must not exceed 49°C. Best results are obtained when material is stored and applied at room temperature 16 to 27°C.

Directions for Use

Ensure all surfaces to be bonded are clean, dry and free from dust, oil and grease before application of adhesive.

Ensure that nozzle points away from all persons and towards the surface to be sprayed. Turn the spray tip so that the arrow points to the dot on the can rim.

Shake can well before using, 5-10 seconds should be sufficient.

Hold the can 15-20 cm away from the surface and apply a uniform coat. When spraying, depress the nozzle fully to avoid spluttering or dripping of adhesive.

Apply adhesive to one surface only, preferably the one being laid down. Allow solvent to evaporate for a few seconds before bonding. This prevents adhesive transfer from one surface to another. Spray Adhesive 75 has a permanent tack. Therefore surfaces can be joined after a few seconds or up to several hours after application.

To prevent nozzle from blocking, at the end of each day turn the can upside down and press the tip until spray is clear from adhesive, and wipe tip.

Clean Up:
 Spray nozzle or excess material may be cleaned with Scotch-Grip Solvent No. 1.
NOTE: Solvent No. 1 is highly flammable. When using solvents for clean up, it is essential that proper safety precautions are observed.

Coverage:
 Approximately 13m² (150 sq. ft.) per container.

Applications

Spray Adhesive 75 is suitable for bonding paper, tissue, cardboard, acetate film, foils, fabrics, plastic sheeting, rubber etc. to themselves, and to metal, wood, glass and rigid plastics.

Spray Adhesive 75 is widely used in textile cutting rooms for holding patterns in place instead of pinning them, and to prevent transfers moving during printing. It is also used for affixing removable labels.

Date :August 1995
Spray 75 Repositionable Adhesive

**Health and Safety
Information**

Refer to product label and Material Safety Data Sheet for health and safety information before using the product.
For information please contact your local 3M Office
www.3M.com

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

3M and Scotch-Weld are trademarks of the 3M Company.

3M

3M Svenska AB Industri

